



## **EcoFleece<sup>®</sup>, moisture and air permeable mesh**

- **Vapour permeable**
- **Only 0.3 mm thick**
- **Very strong**
- **Resistant to chemicals**
- **Easy to process**

To be fitted over a wooden base floor when EcoPearls<sup>®</sup> ecological levelling granules are foreseen to be used. EcoFleece<sup>®</sup> will prevent the EcoPearls<sup>®</sup> from trickling away through the wood flooring.

In an angle of 90° to the direction of the wooden floor boards, roll out the widths of EcoFleece<sup>®</sup> besides each other, overlap the joints with 20 cm and staple them to the wooden surface.



# PRODUCT SPECIFICATIONS

## TECHNICAL DATA

Article number	148.700
Thickness/tolerance (mm)	0.3
Size (cm)/tolerance (mm)	1200 x 50.000 ± 1 mm
Raw material(s) combinations	Polypropylene
Colour	Natural white
Weight per m <sup>2</sup> (kg)	0.05
Weight per roll (kg)	3
Density (kg/m <sup>3</sup> )	167

## APPLICATION

EcoFleece® is a soft, breathable fibre cloth for wooden subfloors used in combination with EcoPearls®.



## ROLL

# 60 m<sup>2</sup>

- Width 120 cm
- Lengte 50 m

**Thickness 0.3 mm**

## PACKAGING

Installation instructions present



**Scan the QR code  
for more info  
about  
Ecofleece®!**

Visit [www.unifloor-underlay.com](http://www.unifloor-underlay.com) for  
the most up-to-date information.