

Fire retardant and acoustic sublayer

- Fire Class: B_{fl-s1}
- High levelling abilities
- Ecological
- Only 3 mm
- Quick & simple to fit
- TOG - 1.2

GreenFloor® is a fire retardant and acoustic sublayer, which can be used underneath a wide variety of Unifloor fast-track subfloor preparation systems.

It forms a perfect match with Jumpax® CP (Cement bonded Panel). This combination will provide more than satisfying acoustics in multiple situations, for instance when fitted over a wooden separation floor.

GreenFloor® is made from pure wool and is therewith completely Ecological.

A polythene sheet should be used under this product as a moisture barrier.



PRODUCT SPECIFICATIONS

TECHNICAL DATA

Article number	158.000
Thickness/tolerance (mm)	3 / ± 0.2
Size (cm)	100 x 2500
Raw material(s) combinations	Sheep wool/Polyester fleece
Colour	Grey/brown
Weight per m ² (kg)	0.250
Weight per roll (kg)	6.3
Density (kg/m ³)	100
Fire class (according to EN13501: 2007)	
Nude test	B _{fl-s1}
Thermal conductivity λ value (W.m/K)	0.40
Thermal resistance R value (m ² .K/W)	0.123
(according to ISO 8302:1991 and EN 12667:2001)	
TOG	1.2
Sound insulation based on R _w = 53 dB (according to ISO 717-1-2013)	
in combination with Redupanel®	R _w = 57 dB (+ 4 dB reduction)
in combination with Jumpax® CP	R _w = 58 dB (+ 5 dB reduction)
Impact sound reduction on wooden floor (according to ISO 10140-3 2010 base from 65 dB)	
in combination with Jumpax® CP	12 dB ΔL _n
in combination with Redupanel®	10 dB ΔL _n
Formaldehyde degree	E-1

APPLICATION

GreenFloor® is a fire retardant and acoustic sublayer, which can be used under Jumpax® CP and Redupanel®.

**GREEN
FLOOR**
UNIFLOOR UNDERLAY SYSTEMS

ROLL

25 m²

• Width 100 cm

Thickness 3 mm

PACKAGING

Installation instructions present
Pallet contents 6 rolls / 150 m²
Pallet size (l x w x h) 1200 x 800 x 1250 mm
Pallet weight 63 kg



Scan the QR code
for more info
about
GreenFloor®!

Visit www.unifloor-underlay.com for
the most up-to-date information.